(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 7 April 2005 (07.04.2005)

PCT

(10) International Publication Number WO 2005/030509 A1

- (51) International Patent Classification⁷: B60G 3/20, 7/00, 13/16, B60K 7/00, F16F 7/104, 15/04
- (21) International Application Number:

PCT/JP2004/014462

(22) International Filing Date:

24 September 2004 (24.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


30 September 2003 (30.09.2003) 2003-341169 JP 9 February 2004 (09.02.2004) 2004-032323 JP

(71) Applicants (for all designated States except US): TOY-OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). AISIN SEIKI KABUSHIKI KAISHA [JP/JP]; 1, Asahi-machi 2-chome, Kariya-shi, Aichi 4488650 (JP).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MIZUTANI, Ryoji [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). TOJIMA, Yuki [JP/JP]; c/o Aisin Seiki Kabushiki Kaisha, 1, Asahi-machi 2-chome, Kariya-shi, Aichi 4488650 (JP). ISOGAI, Shigetaka [JP/JP]; c/o Aisin Engineering Co., Ltd., 1-15, Hachiken-cho, Kariya-shi, Aichi 4488605 (JP). TORII, Atsushi [JP/JP]; c/o Aisin Seiki Kabushiki Kaisha, 1, Asahi-machi 2-chome, Kariya-shi, Aichi 4488650 (JP). SAKURAI, Junichiro [JP/JP]; c/o Aisin Seiki Kabushiki Kaisha, 1, Asahi-machi 2-chome, Kariya-shi, Aichi 4488650 (JP).
- (74) Agents: FUKAMI, Hisao et al.; Fukami Patent Office, Mitsui Sumitomo Bank Minamimorimachi Bldg., 1-29, Minamimorimachi 2-chome, Kita-ku, Osaka-shi, Osaka 5300054 (JP).

[Continued on next page]

(54) Title: WHEEL SUPPORTING APPARATUS IMPROVING RIDE COMFORT OF VEHICLE



(57) Abstract: A wheel supporting apparatus (200) includes dampers (140, 150), ball joints (160, 170), a knuckle (180), an upper arm (210), and a lower arm (220). The dampers (140, 150) are attached to a case (60) of an in-wheel motor (IWM) in the top-bottom direction (DR1) of the vehicle's body and are connected respectively to the ball joints (160, 170). The upper arm (210) and the lower arm (220) have respective one-ends connected to respective dampers (140, 150) via the ball joints (160, 170) and respective other ends pivotably fixed to the vehicle's body. The knuckle (180) is connected to the ball joints (160, 170) to rotatably support a wheel hub (20) via hub bearings (11, 12).

A1 WO 2005/030509

WO 2005/030509 A1

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.